
PMC PREMIUM GLOSS HI WHITE PP30F WG62

Country of manufacture:	Thailand
--------------------------------	----------

Applications:	Designed for a wide range of labels and stickers, with a glossy finish for general-purpose application.
----------------------	---

Product components

Face	Super white with glossy surface, cast coated and mirror finished printing paper.
------	---

Adhesive (PP30F):	General-purpose permanent adhesive, with very good water and aging resistance. Featuring excellent adhesion to low surface energy substrates.
-------------------	---

Liner (WG62):	Super-calendered White Glassine paper.
---------------	--

TECHNICAL SPECIFICATIONS

Property	Grammage	Thickness
Face	80gsm	82 micron (3.2 mil)
Liner	60gsm	54 micron (2,1 mil)
Total	161gsm, $\pm 10\%$	156 micron, $\pm 10\%$

ADHESIVE

Property

Initial Tack	Glass	FTM 9	≥ 11,0	N/25 mm
Initial Tack	Stainless Steel	FTM 9	≥ 10,5	N/25 mm
Adhesion to	Stainless Steel	FTM 2 20 minute 90° peel	≥ 5,0	N/25 mm

LINER

Minimum Service Temperature	-40 °C	-40 °F
Maximum Service Temperature	120 °C	248 °F
Minimum Application Temperature	-5 °C	23 °F

CERTIFICATES

-
- US FDA 21 CFR 175. 105 (Adhesive) for indirect food contact packaging and processing.
-

B&F Papers has endeavoured to ensure this information is correct; however, we do not accept liability for any error or omission. We reserve the right to update this information without prior notice.

Shelf Life: 1 year if store in 22 °C and 50% RH condition. The product must be stored in shady or cool place and do not expose to sunlight directly.

These characteristics are average values supplied for guidance purposes.

Note: It is the user's responsibility to test all stock, prior to use, whether the product is suitable for intended application.

