

## PMC DT TOP PREMIUM PP33C WG62

---

<b>Country of manufacture:</b>	Thailand
--------------------------------	----------

---

<b>Applications:</b>	Designed for use in thermal sensitive printing systems. Typical applications are bar code labels for food packaging; industrial bar coding and tracking where good long-term smudge resistance is required.
----------------------	---

---

### Product components

---

Face:	Premium top coated thermal paper with excellent preservation, offering superior resistance and sharp image to moisture, fat, oil, alcohol and other solvents.
-------	---

---

Adhesive (PP33C):	General-purpose permanent adhesive. Featuring excellent adhesion to low surface energy substrates.
-------------------	--

---

Liner (WG62):	Super calendered White Glassine paper
---------------	---------------------------------------

---



## TECHNICAL SPECIFICATIONS

Property	Grammage	Thickness
Face	70gsm	72 micron (2,8 mil)
Liner	62gsm	54 micron (2,1 mil)
Total	151gsm, ±10%	146 micron, ±10%

## ADHESIVE

Property			
Initial Tack	Glass	FTM 9	≥ 12,5 N/25 mm
Initial Tack	Stainless Steel	FTM 9	≥ 12 N/25 mm
Adhesion to	Stainless Steel	FTM 2 20 minute 90° peel	≥ 6,5 N/25 mm
Minimum Service Temperature		-40 °C	-40 °F
Maximum Service Temperature		120 °C	248 °F
Minimum Application Temperature		-5 °C	23 °F

## CERTIFICATES

- US FDA 21 CFR 175.105 (Adhesive) for indirect food contact packaging and processing.
- European Toy Safety Legislation 88/278/EEC, CEN EN71, Part 3

B&F Papers has endeavoured to ensure this information is correct; however, we do not accept liability for any error or omission. We reserve the right to update this information without prior notice.

Shelf Life: 2 years if store in 22°C and 50% RH condition. The product must be stored in shady or cool place and do not expose to sunlight directly.

These characteristics are average values supplied for guidance purposes.

**Note: It is the user's responsibility to test all stock, prior to use, whether the product is suitable for intended application.**

