

## ADESTOR DT TOP+ REMOVABLE SA234 WG62

---

**Country of manufacture:** Spain

---

**Applications:** Barcode labels for pre-packed food, retail and logistics. Used wherever high stability and image resistance is required to protect against humidity, heat and sunlight.

---

### Product components

---

**Face (DT Top+):** Top coated thermal paper with back barrier. Resistant to grease, moisture, plasticisers and UV light.

---

**Adhesive (SA234):** Acrylic emulsion removable adhesive with **high cohesion** and medium adhesion and tack. Ideal for tight mandrel labelling or different types of reusable transport boxes and trays in logistics and other surfaces used in retail such as glass, ceramic, plastic.

---

**Liner (WG62):** Super-calendared white translucent glassine paper especially designed for automatic labelling applications and photocell dispensing systems. This liner provides good tear resistance and smooth and regular thickness.

---

**Printing techniques:** Suitable for printing on conventional offset, offset UV, letterpress (conventional and UV), UV flexo, flexo solvent base depending on the ink.

---

## FACE

Property	Norm	Units	Value	Tolerance
Substance	ISO 536	g/m <sup>2</sup>	72	67 - 77
Thickness	ISO 534	µm	73	67 - 79
Bekk smoothness	ISO 5627	S	≥ 500	
Brightness ISO	ISO 2470	%	≥ 80	
Tensile strength MD/CD	ISO 1924	kN/M	≥ 3,59 / ≥ 1,63	

## ADHESIVE

Property	Norm	Units	Value	Tolerance
Adhesion (Peel 180° 20' / stainless steel)	FTM 1	N/25mm	12	>12
Adhesion (Peel 180° 24h / Kraft)	FTM 1	N/25mm	5	>5
Adhesion (Peel 180° 24h / PE)	FTM 1	N/25mm	4	>4
Shear (1kg, in <sup>2</sup> / glass)	FTM 8	Min.	60	>60
Tack (Quick stick stainless steel)	FTM 9	N	7	>7
Minimum labelling temperature		°C	-35	
Minimum service temperature		°C	-40	
Maximum service temperature		°C	+60	

## LINER

Property	Norm	Units	Value	Tolerance
Substance	ISO 536	g/m <sup>2</sup>	62	59-65
Thickness	ISO 534	µm	52	49-55



## CERTIFICATES

---

### Face

---

- FSC® MIX
- Contact with Foodstuff (BfR XXXVI) – Face and Liners (paper)
- EN 71 – 3 Toy Safety
- Packaging and packaging waste Directive 94/62/CE
- Electric and electronic equipment (RoHS)

### Adhesive

---

- German Recommendation BfR XIV (ISEGA) - Adhesives

### Liner

---

- Contact with Foodstuff (BfR XXXVI) – Face and Liners (paper)
  - Packaging and packaging waste Directive 94/62/CE
  - EN 71 – 3 Toy Safety
  - Electric and electronic equipment (RoHS)
- 



B&F Papers has endeavoured to ensure this information is correct; however, we do not accept liability for any error or omission. We reserve the right to update this information without prior notice.

Shelf Life: From the date of manufacture 2 years in 20°C and RH 50%. These characteristics are average values supplied for guidance purposes.

**Note: It is the user's responsibility to test all stock, prior to use, whether the product is suitable for intended application.**

