ADESTOR DT TOP+ ULTRA REMOVABLE RA678 YG62

Country of manufacture:	Spain				
Applications:	Barcode labels for pre-packed food, retail and logistics. Used wherever high stability and image resistance is required to protect against humidity heat and sunlight.				
Product components					
Face (DT Top+):	Top coated thermal paper with back barrier. Resistant to grease, moisture, plasticisers and UV light.				
Adhesive (RA678):	Acrylic removable adhesive with clean removability from most surfaces.				
Liner (YG62):	Super-calendared yellow translucent glassine paper especially designed for automatic labelling applications and photocell dispensing systems. This liner provides good tear resistance and smooth and regular thickness.				
Printing techniques:	Suitable for printing on conventional offset, offset UV, letterpress (conventional and UV), UV flexo, flexo solvent base depending on the ink.				



FACE

Property	Norm	Units	Value	Tolerance
Substance	ISO 536	g/m²	72	67 - 77
Thickness	ISO 534	μm	73	67 - 79
Bekk smoothness	ISO 5627	S	≥ 500	
Brightness ISO	ISO 2470	%	≥ 80	
Tensile strength MD/CD	ISO 1924	kN/M	≥ 3,59 / ≥ 1,63	

ADHESIVE

Property	Norm	Units	Value	Tolerance
Adhesion (Peel stainless steel 1 week)	FTM 1	N/25mm	1,7	1 – 2,9
Shear (kg, in²/glass)	FTM 8	Min	120	≥ 60
Tack (Quick Stick stainless steel)	FTM 9	Ν	1,2	0,7 - 1,7
Minimum labelling temperature		°C	5	
Minimum service temperature		°C	-20	
Maximum service temperatur	e	°C	+80	

LINER

Property	Norm	Units	Value	Tolerance
Substance	ISO 536	g/m²	62	59-65
Thickness	ISO 534	μm	52	49-55



Face

- FSC® MIX
- Contact with Foodstuff (BfR XXXVI) Face and Liners (paper)
- EN 71 3 Toy Safety
- Packaging and packaging waste Directive 94/62/CE
- Electric and electronic equipment (RoHS)

Adhesive

- EN 71 3 Toy Safety
- Packaging and packaging waste Directive 94/62/CE

Liner

- Contact with Foodstuff (BfR XXXVI) Face and Liners (paper)
- Packaging and packaging waste Directive 94/62/CE
- EN 71 3 Toy Safety
- Electric and electronic equipment (RoHS)





B&F Papers has endeavoured to ensure this information is correct; however, we do not accept liability for any error or omission. We reserve the right to update this information without prior notice.

Shelf Life: From the date of manufacture 1 year in 20°C and RH 50%. These characteristics are average values supplied for guidance purposes.

Note: It is the user's responsibility to test all stock, prior to use, whether the product is suitable for intended application.

