

PRODUCT

ADESTOR DT TC REMOVABLE RA678 YG62

Manufacturer:	Lecta
Website:	www.adestor.com
Country of manufacture:	Barcelona
Applications:	Barcode labels for pre-packed food, retail and logistics. Used wherever high stability and image resistance is required to protect against humidity, heat and sunlight.

Product components

Facestock (DT TC): Top coated thermal paper with back barrier. Resistant to grease, moisture, plasticisers and UV light.

Adhesive (RA678): Acrylic removable adhesive with clean removability from most surfaces. Trial is recommended when using this adhesive in new or unknown surfaces.

Liner (WG62): Super-calendered white translucent glassine paper especially designed for automatic labelling applications and photocell dispensing systems. This liner provides good tear resistance and smooth and regular thickness.

Printing techniques: Suitable for printing on conventional offset, offset UV, letterpress (conventional and UV), UV flexo, flexo solvent base.

B&F Papers has endeavoured to ensure this information; however, we do not accept liability for any error or omission. We reserve the right to update this information without prior notice.

FACESTOCK

Property	Units	Value	Tolerance
Substance	g/m ²	72	67 - 77
Thickness	µm	73	67 - 79
Bekk smoothness	S	≥ 500	
Brightness ISO	%	≥ 80	
Tensile strength MD/CD	kN/M	≥ 3.59 / ≥ 1.63	

ADHESIVE

Property	Units	Value	Tolerance
Adhesion (Peel 180° 20'/stainless steel)	N/25mm	18.4	≥ 14.7
Shear (kg, in ² /glass)	Min	750	≥ 500
Tack (Quick Stick stainless steel)	N/25mm	13.5	≥ 11
Minimum labelling temperature	°C	0	
Minimum service temperature	°C	-20	
Maximum service temperature	°C	+60	

LINER

Property	Units	Value	Tolerance
Substance	g/m ²	62	59-65
Thickness	µm	52	49-55

Shelf Life: From the date of manufacture 1 year in 20°C and RH 50%
These characteristics are average values supplied for guidance purposes

Note: It is recommended that all pressure sensitive materials are trialled prior to printing.