

PRODUCT

ADESTOR HI GLOSS 80 REMOVABLE RA678 WG62

Manufacturer:	Lecta
Website:	www.adestor.com
Country of manufacture:	Barcelona
Applications:	High resolution standard gloss label for multicolour printing. Extensively used in the food and beverage industry, logistics, stationery and cosmetic products.

Product components

Facestock (HI GLOSS 80): Gloss coated wood free paper.

Adhesive (RA678): Acrylic removable adhesive with clean removability from most surfaces. Trial is recommended when using this adhesive in new or unknown surfaces.

Liner (WG62): Super-calendered white translucent glassine paper especially designed for automatic labelling applications and photocell dispensing systems. This liner provides good tear resistance and smooth and regular thickness.

Printing techniques: Suitable for printing on flexo (all types), letterpress (conventional and UV), conventional offset, offset UV, screen printing, hot stamping, thermal transfer, laser.

B&F Papers has endeavoured to ensure this information; however, we do not accept liability for any error or omission. We reserve the right to update this information without prior notice.

FACE STOCK

Property	Units	Value	Tolerance
Substance	g/m ²	90	± 4%
Thickness	µm	78	± 4
Bekk smoothness	S	≥ 700	≥ 300
Brightness ISO	%	93	± 2
Opacity	%	90	- 2
Whiteness CIE	%	117	± 3
Paper gloss 20°	%	66	± 5
Tensile strength MD/CD	kN/M	5.2	- 0.5

ADHESIVE

Property	Units	Value	Tolerance
Adhesion (Peel 180° 20'/stainless steel)	N/25mm	1.7	1 - 2.9
Shear (1kg, in ² /glass)	Min	120	≥ 60
Tack (Quick Stick stainless steel)	N	1.2	0.7 - 1.7
Minimum labelling temperature	°C	5	
Minimum service temperature	°C	-20	
Maximum service temperature	°C	+80	

LINER

Property	Units	Value	Tolerance
Substance	g/m ²	62	59 - 65
Thickness	µm	52	49 - 55

Shelf Life: From the date of manufacture 1 year in 20°C and RH 50%
 These characteristics are average values supplied for guidance purposes

Note: It is recommended that all pressure sensitive materials are trialled prior to printing.