

PRODUCT

ADESTOR LASER 70 A-251 KL55

Manufacturer:	Lecta
Website:	www.adestor.com
Country of manufacture:	Barcelona
Applications:	Suitable for laser and inkjet printing and photocopying machines.

Product components

Facestock (LASER 70):	Uncoated wood free paper guaranteed for laser printing.
Adhesive (A-251):	General use acrylic permanent adhesive including smooth and slightly rough or curved surfaces.
Liner (KL55):	White liner guaranteed for laser printing. For the conversion of reels to sheets.

Printing techniques:	Suitable for printing on flexo (all types), letterpress (conventional and UV), conventional offset, offset UV, screen printing, hot stamping, laser.
-----------------------------	--

B&F Papers has endeavoured to ensure this information; however, we do not accept liability for any error or omission. We reserve the right to update this information without prior notice.



FACESTOCK

Property	Units	Value	Tolerance
Substance	g/m ²	70	± 4%
Thickness	µm	90	± 5
Brightness ISO	%	103	± 2
Opacity	%	91	- 2
Whiteness CIE	%	143	± 5
Tensile strength MD/CD	kN/M	≥ 3.2 / ≥ 1.9	- 2

ADHESIVE

Property	Units	Value	Tolerance
Adhesion (Peel 180° 20'/ stainless steel)	N/25mm	15.4	≥ 12.3
Shear (1kg, in ² /glass)	Min	100	≥ 60
Tack (Quick Stick stainless steel)	N	10.3	≥ 7.8
Minimum labelling temperature	°C	+5	
Minimum service temperature	°C	-20	
Maximum service temperature	°C	+80	

LINER

Property	Units	Value	Tolerance
Substance	g/m ²	62	59 - 65
Thickness	µm	52	49 - 55
Tensile strength MD/CD	kN/M	≥ 3.8 / ≥ 1.6	

Shelf Life: From the date of manufacture 1 year in 20°C and RH 50%

These characteristics are average values supplied for guidance purposes

Note: It is recommended that all pressure sensitive materials are trialled prior to printing.