

PRODUCT

---

**PMC BOPP GLOSS WHITE TC PP32C WG62**

---

<b>Manufacturer:</b>	PMC Label Materials Co. Ltd
<b>Website:</b>	www.pmlabel.com
<b>Country of manufacture:</b>	Thailand
<b>Applications:</b>	For highly decorative labels on food, cosmetics, toiletries, automotive lubricants and household products where durability and resistance to moisture and chemicals required. It is advisable to test the product with the end-use conditions during the qualification to ensure it meets specific requirements.

**Product components**

---

Facestock (GLOSS WHITE TC):	Gloss white, top coated, biaxially polypropylene film.
Adhesive (PP32C):	General purpose permanent adhesive, with excellent aging resistance. Featuring good tack to low surface energy.
Liner (WG62):	Super calendered White Glassine paper

---

B&F Papers has endeavoured to ensure this information; however, we do not accept liability for any error or omission. We reserve the right to update this information without prior notice.



## TECHNICAL SPECIFICATIONS

Property	Grammage	Thickness
Facestock	46.4gsm	58 micron (2.3 mil)
Liner	60gsm	55 micron (2.2 mil)
Total	128.4 gsm, ±10%	134 micron, ±10%

## ADHESIVE

Property				
Initial Tack	Glass	FTM 9	≥ 12.0	N/25 mm
Initial Tack	Stainless Steel	FTM 9	≥ 11.5	N/25 mm
Adhesion to	Stainless Steel	FTM 2 20 minute 90° peel	≥ 6.0	N/25 mm

Minimum Service Temperature	-40 °C	-40 °F
Maximum Service Temperature	120 °C	248 °F
Minimum Application Temperature	-5 °C	23 °F

Shelf Life: 1 year if stored in 22°C and 50% RH condition. The product must be stored in a shady or cool place and not directly exposed to sunlight. These characteristics are average values supplied for guidance purposes.

**Note: It is recommended that all pressure sensitive materials are trialled prior to printing.**