

PRODUCT

---

**PMC FLUORO PINK PP33F WG62**

---

**Manufacturer:** PMC Label Materials Co. Ltd

---

**Website:** [www.pmlabel.com](http://www.pmlabel.com)

---

**Country of manufacture:** Thailand

---

**Applications:** Designed for general purpose label for eye catching applications such as instructional, promotional and POS label. It is advisable to test the product with the end-use conditions during the qualification to ensure it meets specific requirements.

**Product components**

---

**Facestock (FLUORO PINK):** One sided fluorescent coloured coated paper.

---

**Adhesive (PP33F):** General purpose permanent adhesive, with very good water and aging resistance. Featuring excellent adhesion to low surface energy substrates.

---

**Liner (WG62C):** Super calendered White Glassine paper.

---

B&F Papers has endeavoured to ensure this information; however, we do not accept liability for any error or omission. We reserve the right to update this information without prior notice.

## TECHNICAL SPECIFICATIONS

Property	Grammage	Thickness
Facestock	72gsm	80 micron (3.1 mil)
Liner	60gsm	54 micron (2.1 mil)
Total	153 gsm, ±10%	154 micron, ±10%

## ADHESIVE

Property				
Initial Tack	Glass	FTM 9	≥ 12.5	N/25 mm
Initial Tack	Stainless Steel	FTM 9	≥ 12.0	N/25 mm
Adhesion to	Stainless Steel	FTM 2 20 minute 90° peel	≥ 6.5	N/25 mm

Minimum Service Temperature	-40 °C	-40 °F
Maximum Service Temperature	120 °C	248 °F
Minimum Application Temperature	-5 °C	23 °F

Shelf Life: 1 year if stored in 22°C and 50% RH condition. The product must be stored in a shady or cool place and not directly exposed to sunlight. These characteristics are average values supplied for guidance purposes.

**Note: It is recommended that all pressure sensitive materials are trialled prior to printing.**