

## PRODUCT

---

### PMC INKJET WHITE GLOSS IJ90 PP33F WG62

---

<b>Manufacturer:</b>	PMC Label Materials Co. Ltd
<b>Website:</b>	www.pmlabel.com
<b>Country of manufacture:</b>	Thailand
<b>Applications:</b>	Mainly used for commercial inkjet printing. Universally printable with dye inks. We recommend checking suitability of this product on your printer before using. It is advisable to test the product with the end-use conditions during the qualification to ensure it meets specific requirements.

---

#### Product components

---

<b>Facestock (IJ90):</b>	Front side has a high gloss, cast coated surface for photorealistic printouts, back side is perfectly suitable for a self-adhesive layer.
<b>Adhesive (PP33F):</b>	General purpose permanent adhesive. Featuring excellent adhesion to low surface energy substrates.
<b>Liner (WG62):</b>	Super calendered White Glassine paper.

---

B&F Papers has endeavoured to ensure this information; however, we do not accept liability for any error or omission. We reserve the right to update this information without prior notice.

## TECHNICAL SPECIFICATIONS

Property	Grammage	Thickness
Facestock	87gsm	104 micron (4.1 mil)
Liner	60gsm	55 micron (2.2 mil)
Total	168 gsm, $\pm 10\%$	178 micron, $\pm 10\%$

## ADHESIVE

Property				
Initial Tack	Glass	FTM 9	$\geq 12.5$	N/25 mm
Initial Tack	Stainless Steel	FTM 9	$\geq 12.0$	N/25 mm
Adhesion to	Stainless Steel	FTM 2 20 minute 90° peel	$\geq 6.5$	N/25 mm

Minimum Service Temperature	-40 °C	-40 °F
Maximum Service Temperature	120 °C	248 °F
Minimum Application Temperature	-5 °C	23 °F

Shelf Life: 1 year if stored in 22°C and 50% RH condition. The product must be stored in a shady or cool place and not directly exposed to sunlight. These characteristics are average values supplied for guidance purposes.

**Note: It is recommended that all pressure sensitive materials are trialled prior to printing.**